

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER ALUMASEAL 123 SELF- ADHESIVE MEMBRANES		PRODUCT IDENTIFICATION NUMBER (PIN) NONE	
PRODUCT USE WATER BARRIER / VAPOUR BARRIER / AIR BARRIER			
MANUFACTURER'S NAME HAL INDUSTRIES INC.		SUPPLIER'S NAME HAL INDUSTRIES INC.	
STREET ADDRESS 9681 - 187TH STREET		STREET ADDRESS 9681 - 187TH STREET	
CITY SURREY		PROVINCE B.C.	
POSTAL CODE V4N - 3N3		EMERGENCY TELEPHONE NO. 604 - 888 - 0777 1- 800 663 - 0076	
POSTAL CODE V4N - 3N3		EMERGENCY TELEPHONE NO. 604 - 888 - 0777 1- 800 663 - 0076	

SECTION 2 - HAZARDOUS AND OTHER INGREDIENTS

INGREDIENTS	CAS NUMBER	LD50 OF INGREDIENT (SPECIFY SPECIES AND ROUTE)	LC50 OF INGREDIENT (SPECIFIC SPECIES)
ASPHALT	8052 - 42 -4	ORAL: LD50> 5000 MG/ KG (RAT) DERMAL: LD50> 2000 MG/KG (RABBIT)	N/A, ACGIH RECOMMENDS FOR ASPHALT FUMES: 5 MG/ M ³ HYDROGEN SULPHIDE, 10 PPM (14 MG/ M ³)
REFINED HEAVY OIL	64741 -96 -4		ACGIH TLV & OSHA OBSERVE 5 MG/ M ³ (CUBIC METER OF AIR) FOR MINERAL OILS
STYRENE - BUTADIENE - STYRENE BLOCK COPOLYMER	9003 - 55-8	This polymer does not present an intrinsic health hazard when processed according to correct working procedures. The limits on the residual monomers are:	RESIDUAL MONOMERS STYRENE TWA : 50 ppm = 215 mg/ M ³ STEL : 100 ppm = 425 mg/ M ³
STYRENE - ISOPRENE - STYRENE BLOCK COPOLYMER	25038 - 32 -8	This polymer does not present an intrinsic health hazard when processed according to correct working procedures. The limits on the residual monomers are:	RESIDUAL MONOMERS STYRENE SAME AS ABOVE ISOPRENE NO LIMIT AVAILABLE NOT CLASSIFIED AS A HUMAN CARCINOGEN
INERT FILLER	NOT REGULATED	N/A	N/A
ALUMINUM FOIL SURFACING	NOT REGULATED	N/A	N/A
GRID STYLE FIBREGLASS SCRIM (YARN)	65997-17-3	N/A	N/A

SECTION 3 - PHYSICAL DATA

PHYSICAL STATE SOLID (ASPHALT COATED, SURFACED SHEETS)	ODOUR AND APPEARANCE SHEET FORMS, COLOURED MINERAL GRANULES/ WHITE TALC OR SAND COVERED. BLACKISH (ASPHALTIC COLOURS ALSO).	SLIGHT PETROLEUM ODOUR	ODOUR THRESHOLD (PPM) NOT AVAIL	
VAPOUR PRESSURE: N/A FOR ASPHALT: <1 KPA AT 38 DEG C	VAPOUR DENSITY NOT APPLICABLE	EVAPORATION RATE: NOT AVAIL	SOFTENING PT. COATING 85 - 105 DEG C	FREEZING POINT (DEG C) -15
PH N/A	SPECIFIC GRAVITY 1.8 - 2.5	COEFF. WATER/OIL DIST. INSOLUBLE IN WATER		NOT VOLATILE

SECTION 4 - FIRE AND EXPLOSION DATA

FLAMMABILITY? YES (X) NO ()		IF YES, UNDER WHICH CONDITION? COMBUSTIBLE IF EXPOSED TO HIGH HEAT AND OPEN FLAMES.	
MEANS OF EXTINCTION: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE FOR SMALL FIRES. FIRE FIGHTING PROCEDURES - USE WATER SPRAY TO COOL FIRE EXPOSED PRODUCT AND AS A PROTECTIVE SCREEN. DO NOT POINT SOLID WATER DIRECTLY INTO BURNING ASPHALT TO AVOID SPREADING. SELF-CONTAINED BREATHING APPARATUS IS ADVISED TO BE WORN TO PROTECT AGAINST POSSIBLE RELEASE OF HYDROGEN SULPHIDE AND SULPHUR DIOXIDE IF MATERIAL IS BURNING.			
FLASH POINT (DEG C) AND METHOD (ASTM D93) 255 - 265		UPPER FLAMMABLE LIMIT (% BY VOLUME) NOT AVAIL.	LOWER FLAMMABLE LIMIT (% BY VOLUME) NOT AVAIL.
ASPHALT'S BOILING POINT : 400 DEG C		HAZARDOUS COMBUSTION PRODUCTS CARBON DIOXIDE, CARBON MONOXIDE, SO _x , H ₂ S AND OTHER ORGANIC VAPOURS	
EXPLOSION DATA		SENSITIVITY TO IMPACT NONE	SENSITIVITY TO STATIC DISCHARGE NONE

SECTION 5 - REACTIVITY DATA

CHEMICAL STABILITY YES (X) NO ()		IF NO, UNDER WHICH CONDITION? STABLE AT AMBIENT CONDITIONS.	
INCOMPATIBILITY WITH OTHER SUBSTANCES YES (X) NO ()			
		IF SO, WHICH ONES? STRONG OXIDIZING AGENTS	
REACTIVITY, AND UNDER WHAT CONDITIONS		EXCESSIVE HEAT APPROACHING FLASH POINT	
HAZARDOUS DECOMPOSITION PRODUCTS		STABLE UNDER NORMAL CONDITIONS. SEE HAZARDOUS COMBUSTION PRODUCTS FOR PRODUCTS OF THERMAL DECOMPOSITION.	

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY (X) SKIN CONTACT	() SKIN ABSORPTION	(X) EYE CONTACT	(X) INHALATION	() INGESTION
EFFECT OF ACUTE EXPOSURE TO PRODUCT: SKIN / EYE CONTACT : IRRITATION INHALATION: FUMES FROM HOT ASPHALT IN CASE OF FIRE MAY CAUSE NAUSEA, HEADACHE AND DIZZINESS.				
EFFECT OF CHRONIC EXPOSURE TO PRODUCT THE MANUFACTURED PRODUCT AS PRODUCED AND WHEN USED UNDER AMBIENT CONDITIONS POSES NO HEALTH HAZARD.				
EXPOSURE LIMITS NOT LISTED BY NIOSH	IRRITANCY OF PRODUCT NOT AVAIL.	SENSITIZATION TO PRODUCT NOT AVAIL.	CARCINOGENICITY NOT LISTED AS CARCINOGENS (IARC)	
TERATOGENICITY NOT AVAIL.	REPRODUCTIVE TOXICITY NOT AVAIL.	MUTAGENICITY NOT AVAIL.	SYNERGISTIC PRODUCTS NOT AVAIL.	

SECTION 7 - PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:		
GLOVES (SPECIFY) : NOT NORMALLY PRACTICAL WASH HANDS AFTER CONTACT.	RESPIRATOR (SPECIFY) : NOT NEEDED UNDER AMBIENT CONDITIONS ORGANIC CANISTER IF HEATING PRODUCT.	EYE (SPECIFY): AVOID EYE CONTACT WITH PRODUCT OR WITH HANDS DURING PRODUCT APPLICATION.
FOOTWEAR (SPECIFY) : PROTECTIVE FOOTWEAR	CLOTHING (SPECIFY) : NORMAL WORK CLOTHING	OTHER (SPECIFY) :
ENGINEERING CONTROLS (SPECIFY, E.G VENTILATION, ENCLOSED PROCESS) : IF PRODUCT IS BEING HEATED OR BURNING PROVIDE SUFFICIENT VENTILATION. (SEE SECTION 4)		
LEAK AND SPILL PROCEDURE: NOT NORMALLY IN LIQUID STATE. N / A		
WASTE DISPOSAL: SEND TO RECYCLER OR INCINERATOR ACCORDING TO FEDERAL, PROVINCIAL AND LOCAL REGULATIONS.		
HANDLING PROCEDURES AND EQUIPMENT: EXERCISE THE USUAL SAFETY PRECAUTIONS WHEN HANDLING PRODUCTS WITH PETROLEUM DISTILLATE. KEEP AWAY FROM IGNITION SOURCES. WASH HANDS THOROUGHLY AFTER SKIN CONTACT.		
STORAGE REQUIREMENTS: STORE IN WELL VENTILATED AREAS AWAY FROM IGNITION SOURCES AND STRONG OXIDIZING MATERIALS.		
SPECIAL SHIPPING INFORMATION:		

SECTION 8 - FIRST AID MEASURES IN CASE OF FIRE CREATED FUMES

SPECIFIC MEASURES	
EYE CONTACT:	FLUSH WITH LARGE AMOUNTS OF WATER WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN CONTACT:	WASH WITH SOAP AND WATER, OR USE BABY OIL OR WATERLESS HAND CLEANER. DO NOT USE SOLVENTS OR THINNERS TO CLEAN THE SKIN, GET MEDICAL ATTENTION IF IRRITATION PERSISTS.
INGESTION:	NOT EXPECTED TO BE A ROUTE OF ENTRY. IF INGESTED GIVE LIQUIDS. DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.
INHALATION:	REMOVE VICTIM TO FRESH AIR. IF BREATHING IS DIFFICULT APPLY CARDIOPULMONARY RESUSCITATION AND GET IMMEDIATE MEDICAL ATTENTION.

SECTION 9 - PREPARATION DATE OF MSDS

PREPARED BY :

" TECHNICAL GROUP"
HAL INDUSTRIES INC.

PHONE NUMBER

604 - 888 - 0777
1-800-663-0076

DATE Jan. 3, 2008

IMPORTANT: The technical information herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of storage, handling and use of product. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as license to operate under recommendation to infringe any patents.