

# NO. 30 SHAKE FELT PLAIN 18" ASTM D4869/CSA A123.3

---

## Description

A heavy-weight asphalt roofing felt made of a specially formulated organic sheet which has been fully saturated with waterproofing asphalt. This sheet is pre-conditioned to lay flat and remain stable during and after installation. Application guidelines are applied 2", 8", 10" and 16" from each outside edge.

## Uses

As shingle underlayment used beneath wood shingles and shakes, as a barrier to wind-driven rain and snow.

## Specifications

Conforms to:	ASTM D4869 Type III and CSA A123.3
Average Breaking Strength:	
Along fibre grain, kN/m (lb/in) of width:	Exceeds: 7 (40)
Across fibre grain, kN/m (lb/in) of width:	Exceeds: 3.5 (20)
Average roll weight, lbs/roll:	40 (approx.)

## Packaging

Roll width:	18"
Roll Contents:	180 sq.ft. (16.7 sq.m.)
Rolls per pallet:	32
Pallets size:	40" x 48"

*The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. The user of such information assumes all risk connected with the use thereof. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.*

Revised 27 Apr, 2011

FE1500.doc